



Transparent LCD Display Specification-InnoGlass

Data \Size	15 inch	19 inch	21.6 inch	22 inch	23.6inch	27 inch	32 inch	44 inch	50 inch	55 inch	65inch	82 inch
Monitor dimensions	366*264*9mm	432*332*9mm	496.6*360.6*8mm	497*377*9mm	545*321*10mm	630*370*15mm	738*467*12mm	998*617*17mm	1129*695*17mm	1265*787*17mm	1536*1000*20mm	1884*1174*20mm
Display dimensions	344*194mm	410*256mm	477*268mm	475 *297 mm	521*293mm	597*336mm	699*393mm	942*529mm	1074*605mm	1210*682mm	1428*800mm	1804*1014mm
Aspect ratio	16:09	16:09	16:09	16:10	16:09	16:09	16:09	16:09	16:09	16:09	16:09	16:09
Pixel arrangement	RECTANGLE	RECTANGLE	RECTANGLE	RECTANGLE	RECTANGLE	RECTANGLE	RECTANGL E	RECTANGL E	RECTANGL E	RECTANGL E	RECTANGL E	RECTANGL E
Resolution	1024*768	1280*1024	1920*1080	1680*1050	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080
RGB	70%	70%	70%	70%	70%	70%	70%	70%	70%	70%	70%	70%
Display colour	16.7M (8-BIT)	16.7M (8-BIT)	16.7M (8-BIT)	16.7M (8-BIT)	16.7M (8-BIT)	16.7M (8-BIT)	16.7M (8-BIT)	16.7M (8-BIT)	16.7M (8-BIT)	16.7M (8-BIT)	16.7M (8-BIT)	16.7M (8-BIT)
Response time	1.3/3.7 (typ.) (tr/td)(ms)	1.3/3.7 (typ.) (tr/td)(ms)	1.3/3.7 (typ.) (tr/td)(ms)	1.3/3.7 (typ.) (tr/td)(ms)	5 (typ.) (tr/td)(ms)	5 (typ.) (tr/td)(ms)	6.5 (typ.) (tr/td)(ms)	6.5 (typ.) (tr/td)(ms)	6.5(typ.) (tr/td)(ms)	5 (typ.) (tr/td)(ms)	6.5 (typ.) (tr/td)(ms)	3.5 (typ.) (tr/td)(ms)
Visual angle	85/85/80/80 (TYP.)(CR>20)	85/85/80/80 (TYP.)(CR>20)	85/85/80/80 (TYP.)(CR>20)	85/85/80/80 (TYP.)(CR>20)	85/85/80/80 (TYP.)(CR>20)	85/85/80/80 (TYP.)(CR>20)	88/88/88/88(TYP.)(C R>20)	88/88/88/88(TYP.)(C R>20)	88/88/88/88(TYP.)(C R>20)	88/88/88/88(TYP.)(C R>20)	89/89/89/89(TYP.)(C R>20)	89/89/89/89(TYP.)(C R>20)
Transparency	23%	23%	23%	23%	23%	23%	23%	23%	23%	23%	23%	25%
	75%~85%	75%~85%	75%~85%	75%~85%	75%~85%	75%~85%	75%~85%	75%~85%	75%~85%	75%~85%	75%~85%	75%~85%
Display depth	9mm	9mm	8mm	9mm	10mm	15mm	12mm	17mm	17mm	17mm	17mm	18.5mm
Weight	0.9KG	1.1KG	1.5KG	1.5KG	1.7KG	1.9KG	4.3KG	10KG	11kg	13kg	17KG	29KG
Touch screen	Optional											
Input	USB\ SD\ VGA\ HDMI											
Possible viewing angles	0°, 90°, 180°, 270°											



Transparent LCD Display Specification-InnoGlass

Data \Size	15 inch	19 inch	21.6 inch	22 inch	23.6inch	27 inch	32 inch	44 inch	50 inch	55 inch	65inch	82 inch
Control mode	Remote											
Supported media files	MPG、MPEG1、MPEG2、MPEG4、AVI、MP4、DIV、TRP、WMV、RM、RMVB、MKV and TS											
Volt	12v	12v	12v	12v	12V	12v	12v	12v	12v	12v	12V	12v
Power	1.2W	1.5w	1.7w	1.7w	2W	2.5w	6.72W	7.2w	8.4w	10w	12W	15w
Workable temperature	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C
Storage temp.	-20°C- 85°C	-20°C- 85°C	-20°C- 85°C	-20°C- 85°C	-20°C- 85°C	-20°C- 85°C	-20°C- 85°C	-20°C- 85°C	-20°C- 85°C	-20°C- 85°C	-20°C- 85°C	-20°C- 85°C

InnoGlass
2017.10.20